

# December 2011 MSS/LPS/SPS Joint Subcommittee Meeting

## ABSTRACT SUBMITTAL FORM

The submission of an abstract is an agreement to complete a final paper for publication and attend the meeting to present this information. Complete all information requested in the author and co-author information sections; the first author listed will receive paper acceptance notices and all correspondence. Abstracts must be submitted electronically; submittal instructions are located in the call for papers. **The abstract deadline date is June 13, 2011.**

### ABSTRACT INFORMATION

Title: Waterhammer Transient Simulation and Model Anchoring for the Robotic Lunar Lander Propulsion System

Submitted for consideration to: ☐ MSS ☐ LPS ☒ SPS

For inclusion in Technical Area: ☒ 1 ☐ 2 ☐ 3 ☐ 4 ☐ 5 ☐ 6

Security Classification of Presentation: ☒ Unclassified

Security Classification of Paper: ☒ Unclassified

Contract Number(s) Under Which Work was Performed: \_\_\_\_\_ ☐ IR&D

Is this paper an update? ☐ Yes ☒ No Has it been presented elsewhere? ☐ Yes ☒ No Is this a student paper? ☐ Yes ☒ No

### AUTHOR INFORMATION

Author/Presenter Name: William B. Stein

Affiliation Jacobs ESTS Group

Address P.O. Box 9030 Marshall Space Flight Center

City Huntsville State AL Zip 35812

Telephone 256.961.1437 Telefax

e-mail: william.b.stein@nasa.gov

2<sup>nd</sup> Author: Huu P. Trinh

Affiliation

Address Marshall Space Flight Center

City Huntsville State AL Zip 35812

Telephone 256.544.2260 Telefax

e-mail: huu.p.trinh@nasa.gov

3<sup>rd</sup> Author: Michael E. Reynolds

Affiliation Jacobs ESTS Group

Address Marshall Space Flight Center

City Huntsville State AL Zip 35812

Telephone 256.961.1892 Telefax

e-mail: michael.e.reynolds@nasa.gov

Additional Author(s): David J. Sharp

Affiliation Jacobs ESTS Group

Address Marshall Space Flight Center

City Huntsville State AL Zip 35812

Telephone 256.544.0368 Telefax

e-mail: david.j.sharp@nasa.gov

### MANAGEMENT APPROVAL

The individual below certifies that the required resources are available to present this paper at the above subject JANNAF meeting.

Responsible Manager authorizing presentation:

Title/Agency:

Telephone Number:

e-mail:

Date:

## December 2011 MSS/LPS/SPS Joint Subcommittee Meeting ABSTRACT SUBMITTAL FORM

### Unclassified Abstract

*(250-300 words; do not include figures or tables)*

Waterhammer transients have the potential to adversely impact propulsion system design if not properly addressed. Waterhammer can potentially lead to system plumbing, and component damage. Multi-thruster propulsion systems also develop constructive/destructive wave interference which becomes difficult to predict without detailed models. Therefore, it is important to sufficiently characterize propulsion system waterhammer in order to develop a robust design with minimal impact to other systems.

A risk reduction activity was performed at Marshall Space Flight Center to develop a tool for estimating waterhammer through the use of anchored simulation for the Robotic Lunar Lander (RLL) propulsion system design. Testing was performed to simulate waterhammer surges due to rapid valve closure and consisted of twenty-two series of waterhammer tests, resulting in more than 300 valve actuations. These tests were performed using different valve actuation schemes and three system pressures.

Data from the valve characterization tests were used to anchor the models that employed MSCSoftware.EASY5 v.2010© to model transient fluid phenomena by using transient forms of mass and energy conservation. The anchoring process was performed by comparing initial model results to experimental data and then iterating the model input to match the simulation results with the experimental data. The models provide good correlation with experimental results, supporting the use of EASY5 as a tool to model fluid transients and provide a baseline for future RLL system modeling.

This paper addresses tasks performed during the waterhammer risk reduction activity for the RLL propulsion system. The problem of waterhammer simulation anchoring as applied to the RLL system is discussed with results from the corresponding experimental valve tests. Important factors for waterhammer mitigation are discussed along with potential design impacts to the RLL propulsion system.